



Underpressure Tee

GENERAL APPLICATION

WSI Stainless Steel Underpressure Tee design to offer Flexibility and Fast to make T connection into new or existing pipe DN 100 – DN 600. With EPDM rubber and All 304 Stainless Steel construction will show the best performance.

TECHNICAL DATA

Size	: DN100 - DN600
Off-take Sizes	: DN80 - DN300
Material	: All Welded AISI 304 Stainless Steel AISI 316 available upon request
Gasket	: EPDM rubber
Max. Operating Pressure	: PN 10
Max. Temperature	: 60 deg C

STANDARD DATA

Nominal Size DN	Off-take Size (mm)	Length (mm)	No. of Bolt
100 - 125	80, 100	400	10
150 - 175	80, 100, 150	400	10
200 - 250	80, 100, 150, 200	400	10
300 - 350	80, 100, 150, 200	600	14
400 - 450	80, 100, 150, 200	600	14
500 - 600	80, 100, 150, 200, 300	800	18

BENEFITS

- Suitable to be drilling while under pressure without water supply shut-off
- Available for any type and size of pipe
- Save time
- No water supply shut-off
- Full circle EPDM gasket seal
- Fully welded



PT.PASTI MAKMURKENCANA
Ruko Kemang Pratama
Jl. Kemang Pratama Raya blok MM - 3, Bekasi - 17116, INDONESIA
P. +6221 - 82425511 F. +6221 - 82417261
www.pastimakmur.com | sales@pastimakmur.com